Volt Aircraft Battery Charger - Product Brief

24



Activator 282

Direct connect and Fully automatic charger for 24 volt military and aviation batteries of all ratings



Extends Battery Life

The Activator 282 is a direct connect, fully automatic 2 Amp charger capable of charging a 24 volt military or aviation battery of any rating from zero to full capacity. It is also a standby maintenance unit without the use of "trickle" charging, thus extending the life and durability of the battery. There is no gassing, heat or other detrimental results of trickle or float charge. The digital voltmeter continuously displays battery voltage during charge and standby.

Features

- Direct Connect Design No charge cables.
- Microprocessor controlled, multistep charge algorithm.
- 8 Amp pulses bring a deeply discharged battery up from zero volts.
- Conditioning mode top charges NiCads and rejuvenates Lead Acid.
- Short cell/over-temp protection, non-responsive battery indication.
- Can be left on indefinitely charges only when required.





Specifications

AC Input: Worldwide 90 to 260 VAC **DC Output:** 8 Amp Pulse, 2.5 Amp Charge P/N: Activator 282 (& 282-300)

NSN: 6130-01-465-2674 Dimensions: 5.5" H x 4.5" W x 3.5" D

Weight: 1.5 lbs

Includes: Padded carrying case, technical

manual, IEC line cord

Cooling fan

Control Description

- AC line cord
- 2 Instruction & rating plate
- 3 Charge (yellow) 4 Ready (green)

- 6 Digital voltmeter, LCD
- 8 On/off switch Test point (external voltmeter)
- 10 Lead Acid NiCad setting
- 6 Overtemp (red) / fault (yellow) 1 Battery quick disconnect knob

Lamar Technologies LLC 14900 40th Ave. NE Marusville. WA 98223 www.lamartech.com 360-651-8869 support@lamartech.com